

TECHNICAL DATASHEET

Pipe Flashings

FOR SLATE & TILE ROOFS

Slate Roof Terminal

Installs in a flash on Slate Roofs

Slate Roof Terminal won't stain or corrode roofs and gutters. The EPDM cone, which is trimmed on site to fit, is ingeniously locked to a high grade and malleable 99.9% pure aluminium base.

The fast economical way to flash a tile roof.

| Pipe External | Roof Pitch | Base Size | Base Type | Code Black EPDM |
|---------------|------------|-------------|-----------|-----------------|
| 50 - 170mm | 0-45° | 500 x 600mm | Aluminium | SDA101 |
| 110 - 200mm | 0-45° | 600 x 600mm | Aluminium | SDA102 |



SDA101/SDA102

Tile Roof Terminal

No more concern about Unprotected Lead

The Tile Roof Terminal has been developed for use where the handling of lead and associated environmental issues are of concern. Combines a long-life, weather-resistant EPDM cone with a grey primed acrylic coated lead base. The unique thermo-baked coating does not affect the lead's malleability, and prevents leaching onto the roof and into gutters, downpipes and the water table.

| Pipe External | Roof Pitch | Base Size | Base Type | Code Black EPDM |
|---------------|------------|-------------|-----------|-----------------|
| 50 - 170mm | 0-45° | 600 x 450mm | Nu-Lead | SNL101 |
| 175 - 330mm | 0-45° | 850 x 550mm | Nu-Lead | SNL103 |



SNL101/SNL103

CAN BE USED WITH: INSULATED CHIMNEYS • SOIL PIPES • VENTILATION PIPES